


**mandeks**

Katalog grla, ugradnih i prolaznih sklopki



# 1 UGRADNE I PROLAZNE SKLOPKE



## PROLAZNA SKLOPKA SV02 300V

2A/250V~

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 61058-1, EN 61058-2-1

## SINGLE-POLE IN-LINE SWITCH SV02 300V

2A/250V~

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 61058-1, EN 61058-2-1



AW10BK

AW10WH



## UGRADNA SKLOPKA SV03 320V

2A/250V~

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 61058-1

## INCORPORATED SWITCH SV03 320V

2A/250V~

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 61058-1



AW15BK

AW15WH

### SKLOPKA TIPKA SV01 330V

2A/250V~

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 61058-1

### SINGLE-POLE PUSH BUTTON SWITCH SV01 330V

2A/250V~

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 61058-1



### NOŽNA SKLOPKA 350V

2A/250V~

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 61058-1, EN 61058-2-1

### THROUGH CORD SINGLE-POLE FOOT SWITCH 350V

2A/250V~

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 61058-1, EN 61058-2-1





2 GRLA


**TERMOPLASTIČNO GRLO E14 50S**

2A/250V~

Temperaturna izdržljivost: 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

 Pričvrščivanje: bezvijčani kontakt, 0,5÷1,5mm<sup>2</sup>

Sukladno normi: EN 60238

**THERMOPLASTIC LAMPHOLDER E14 50S**

2A/250V~

Rated temperature: 210 °C

Overvoltage category: II

Material: thermoplastic

 Fixing: screwless contact, 0,5÷1,5mm<sup>2</sup>

In accordance with: EN 60238


**AW20BK**

**AW20WH**

**TERMOPLASTIČNO GRLO ZA LUSTER E14 60S**

2A/250V~

Temperaturna izdržljivost: 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

 Pričvrščivanje: bezvijčani kontakt, 0,5÷1,5mm<sup>2</sup>

Sukladno normi: EN 60238

**THERMOPLASTIC LAMPHOLDER WITH RING E14 60S**

2A/250V~

Rated temperature: 210 °C

Overvoltage category: II

Material: thermoplastic

 Fixing: screwless contact, 0,5÷1,5mm<sup>2</sup>

In accordance with: EN 60238


**AW22BK**

**AW22WH**



### KERAMIČKO GRLO E14 70

2A/250V~

Temperaturna izdržljivost: 200 °C

Prenaponska kategorija: II

Materijal: keramika

Pričvršćivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### PORCELAIN LAMPHOLDER E14 70

2A/250V~

Rated temperature: 200 °C

Overvoltage category: II

Material: porcelain

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238



AW23WH

### KERAMIČKO GRLO E14 ZA PLAFONJERE 70

2A/250V~

Temperaturna izdržljivost: 200 °C

Prenaponska kategorija: II

Materijal: keramika

Pričvršćivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### PORCELAIN LAMPHOLDER E14 WITH METAL PLATE 70

2A/250V~

Rated temperature: 200 °C

Overvoltage category: II

Material: porcelain

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238



AW25WH




**TERMOPLASTIČNO GRLO E27 80S**

4A/250V~

Temperaturna izdržljivost: 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

 Pričvrščivanje: bezvijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

**THERMOPLASTIC LAMPHOLDER E27 80S**

4A/250V~

*Rated temperature: 210 °C*
*Overvoltage category: II*
*Material: thermoplastic*
*Fixing: screwless contact, 0,5÷2,5mm<sup>2</sup>*
*In accordance with: EN 60238*

**AW31BK**

**AW31WH**

**TERMOPLASTIČNO GRLO E27 ZA LUSTER 81S**

4A/250V~

Temperaturna izdržljivost: 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

 Pričvrščivanje: bezvijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

**THERMOPLASTIC LAMPHOLDER E27 WITH RING 81S**

4A/250V~

*Rated temperature: 210 °C*
*Overvoltage category: II*
*Material: thermoplastic*
*Fixing: screwless contact, 0,5÷2,5mm<sup>2</sup>*
*In accordance with: EN 60238*

**AW32BK**

**AW32WH**

### KERAMIČKO GRLO E27 95

4A/250V~

Temperaturna izdržljivost: 180 °C

Prenaponska kategorija: II

Materijal: keramika

Pričvršćivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### PORCELAIN LAMPHOLDER E27 95

4A/250V~

Rated temperature: 180 °C

Overvoltage category: II

Material: porcelain

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238



AW33WH

### KERAMIČKO GRLO E27 SA METALNOM MATICOM 90

4A/500V~

Temperaturna izdržljivost: 270 °C

Prenaponska kategorija: III

Materijal: keramika

Pričvršćivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### PORCELAIN LAMPHOLDER E27 WITH METAL RING 90

4A/500V~

Rated temperature: 270 °C

Overvoltage category: III

Material: porcelain

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238



AW34WH




**KERAMIČKO GRLO E27 ZA PLAFONJERE 95**

4A/250V~

Temperaturna izdržljivost: 180 °C

Prenaponska kategorija: II

Materijal: keramika

 Pričvrščivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

**PORCELAIN LAMPHOLDER E27 WITH METAL PLATE 95**

4A/250V~

Rated temperature: 180 °C

Overvoltage category: II

Material: porcelain

 Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238


**AW35WH**

**KERAMIČKO GRLO E40 110/N**

16A/750V

Temperaturna izdržljivost: 300 °C

Prenaponska kategorija: III

Materijal: keramika

 Pričvrščivanje: vijčani kontakt, 1,5÷4mm<sup>2</sup>

Sukladno normi: EN 60238

**PORCELAIN LAMPHOLDER E40 110/N**

16A/750V

Rated temperature: 300 °C

Overvoltage category: III

Material: porcelain

 Fixing: screw contact, 1,5÷4mm<sup>2</sup>

In accordance with: EN 60238


**AW40WH**

### MESINGANO GRLO E27 890

4A/250V~

Temperaturna izdržljivost: 230 °C

Prenaponska kategorija: II

Materijal: mesing

Pričvrščicanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### BRASS PLATED LAMPHOLDER E27 890

4A/250V~

Rated temperature: 230 °C

Overvoltage category: II

Material: brass plated

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238

AW51WH

### MESINGANO GRLO E27 ZA LUSTER 891

4A/250V~

Temperaturna izdržljivost: 230 °C

Prenaponska kategorija: II

Materijal: mesing

Pričvrščicanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### BRASS PLATED LAMPHOLDER WITH RING E27 891

4A/250V~

Rated temperature: 230 °C

Overvoltage category: II

Material: brass plated

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238

AW52WH




**TERMOPLASTIČNO VIJČANO GRLO E14**

2A/250V~

Temperaturna izdržljivost: 190 °C

Prenaponska kategorija: II

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 60238

**THERMOPLASTIC SCREW CONTACT  
LAMPHOLDER E14**

2A/250V~

Rated temperature: 190 °C

Overvoltage category: II

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 60238


**AW70BK**

**AW70WH**

**TERMOPLASTIČNO VIJČANO GRLO ZA LUSTER E14**

2A/250V~

Temperaturna izdržljivost: 190 °C

Prenaponska kategorija: II

Materijal: termoplastika

Pričvršćivanje: vijčani kontakt

Sukladno normi: EN 60238

**THERMOPLASTIC SCREW TYPE CONTACT  
LAMPHOLDER E14 WITH RING**

2A/250V~

Rated temperature: 190 °C

Overvoltage category: II

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 60238


**AW72BK**

**AW72WH**

**TERMOPLASTIČNO VIJČANO GRLO E27**

4A/250V~

Temperaturna izdržljivost: 190 °C - 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

Pričvršćicanje: vijčani kontakt

Sukladno normi: EN 60238

**THERMOPLASTIC SCREW CONTACT LAMPHOLDER E14**

4A/250V~

Rated temperature: 190 °C - 210 °C

Overvoltage category: II

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 60238



AW81BK



AW81WH

**TERMOPLASTIČNO VIJČANO GRLO ZA LUSTER E27**

4A/250V~

Temperaturna izdržljivost: 190 °C - 210 °C

Prenaponska kategorija: II

Materijal: termoplastika

Pričvršćicanje: vijčani kontakt

Sukladno normi: EN 60238

**THERMOPLASTIC SCREW TYPE CONTACT LAMPHOLDER E27 WITH RING**

4A/250V~

Rated temperature: 190 °C - 210 °C

Overvoltage category: II

Material: thermoplastic

Fixing: screw contact

In accordance with: EN 60238



AW82BK



AW82WH





**N/Ž PODNOŽJE S GRLOM E27 RAVNO**

Materijal: termoplastika

Pričvrščivanje: sa 66mm vijcima

**E27 SPOT LIGHT WITH STRAIGHT BASE**

*Material: thermoplastic*

*Fixing: with screw 66mm*



**Aw90WH**



**N/Ž PODNOŽJE S GRLOM E27 KOSO**

Materijal: termoplastika

Pričvrščivanje: sa 66mm vijcima

**E27 SPOT LIGHT WITH INCLINED BASE**

*Material: thermoplastic*

*Fixing: with screw 66mm*



**Aw91WH**



### KERAMIČKO GRLO E27 SA ZAŠTITNOM KAPOM

4A/500V~

Temperaturna izdržljivost: 270 °C

Prenaponska kategorija: III

Materijal: keramika

Pričvršćivanje: vijčani kontakt, 0,5÷2,5mm<sup>2</sup>

Sukladno normi: EN 60238

### PORCELAIN LAMPHOLDER E27 WITH SNAP-ON DOME

4A/500V~

Rated temperature: 270 °C

Overvoltage category: III

Material: porcelain

Fixing: screw contact, 0,5÷2,5mm<sup>2</sup>

In accordance with: EN 60238



AW36WH





**TEM Mandeks d.o.o.**  
Varaždinska 2, 88220  
Široki Brijeg, Bosna i Hercegovina  
**Tel:** +387 39 704 414  
**Faks:** +387 39 706 763  
**E-mail:** [info@mandeks.ba](mailto:info@mandeks.ba)  
**Web:** [www.mandeks.ba](http://www.mandeks.ba)